

Tiller Aro 2+1 Aro 60S C3



Features

- > 6 monobloc tines, Ø 320 mm (straight, forged and dismantable knives) + discs
- > Gearbox: 2 gears forward + 1 reverse (steel sprockets)
- > New belt tension clutch, with cable set for life
- > Wide steel tines cover plates
- > Foldable, height and lateral adjustable handlebar
- > Waterproof seals on transmission shaft Ø 25 mm
- > Transmission by chain, dismantable and greased
- > Spur
- > Foldable front wheel

Technical information

Recommended area	< 2500 m ²
Working width	60 - 80 cm
Gears	2 forward - 1st: 60 to 80 rpm - 2st: 140 to 160 rpm 1 Reverse
Working tools	6 tines Ø 320 mm (4 monobloc tines + 2 additional tines) + discs
Weight	58 kg
Engine	Subaru EP17
Displacement	169 cc
Net power ¹	4,2 KW to 4000 rpm
Nominal power	3,7 KW to 3400 rpm
Fuel tank capacity	3,4 L
Oil tank capacity	0,6 L

Practical information

Packaging	Carton box
Box dimensions (LxHxh)	830 x 600 x 820 mm
Quantity per pallet	12
Pallet dimensions (LxHxh)	1650 x 1200 x 2630 mm
Product code	3000023005
Gen code	3700304810462

For accessories or options please contact us
or visit our website www.pubert.com

¹ The Engine power output indicated in this document is a net value measured by testing a motor according to the SAEJ1349 norm at a given engine evolution speed. The power of another motor may be different from the indicated value. The true power of a motor depends on several factors such as engine evolution speed, temperature, humidity, atmospheric pressure, maintenance and others.

